PFAS EQUIPMENT DAILY INSPECTION SHEET

Employee Name: _____ **Week Of:** _____

Harness Serial #: _____ **Fall Arrest Serial #:** _____

	Monday		*Tuesday*		*Wednesday*		*Thursday*		*Friday*		*Saturday*		*Sunday*	
	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL
BELT/ HARNESS														
Webbing: No tears, cuts, burns, excessive UV damage or chemical exposures	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Buckles and Hardware: No deformities, cracks, burs, rust, missing springs, or abnormal wear	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
D-Rings: No cracks, wear, rust or deformity	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Harness: Proper size and fit, fall indicator not deployed	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Is the harness within 5 years of manufactured date and have all original tags present and legible	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
LANYARDS														
Grommets: No excessive wear or deformity	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Snap Hooks/Carbineers: 16kN Gate Strength and Open/Close properly, no excessive; wear, deformity, rust or corrosion	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Rope or Strap: No cuts, wear, fraying, chaffing, bunny fur, chemical exposure, ripping, excessive UV damage or unraveling braid	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Is the lanyard within 5 years of manufactured date and have all original tags present and legible. Fall indicator not deployed	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
HARDWARE														
Snap Hooks/Carbineers/Spreaderbar: 16kN Gate Strength and Open/Close properly, no excessive; wear, deformity, rust or corrosion	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Safety Climb: Open/Close properly, no excessive wear, deformity, rust or corrosion	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐