

# IMAFLEX Can Block XSB

## Textured v-TIF Fumigation Mulch Film

### DESCRIPTION:

Modified HDPE v-TIF grade barrier film for fumigation applications

Available in 0.8 mil Black and .9 mil White on Black to maximize coverage and minimize disposal costs.

High tensile strength for mechanical laying.

Embossing provides the elasticity to enable tight formation over raised beds.

Excellent moisture retention and weed reduction in addition to barrier to fumigation gases

Widths from 36 inch to 66 inch.

### APPLICATION:

Raised-bed row mulching of vegetable crops, strawberries, melons, peppers.

PROPERTY	UNITS	TYPICAL VALUE	TEST METHOD
Thickness	mil	0.8	ASTM D-374
Opacity		100%	
Tensile @ yield,	MD psi	2320	ASTM D-882
	TD psi	1890	
Ultimate Tensile,	MD psi	4230	ASTM D-882
	TD psi	3370	
Break Elongation,	MD %	355	ASTM D-882
	TD %	400	
1% Secant Modulus,	MD psi	44605	ASTM D-882
	TD psi	48200	
Elmendorf Tear,	MD g/mil	146	ASTM D-1922
	TD g/mil	226	
Dart Drop (method A)	g/mil	235	ASTM D-1709

Imaflex makes no warranties in regard to the material (s) described herein, except that such material(s) shall conform to Imaflex's specifications either as in effect at the time of shipment or incorporated herein.