

# IMAFLEX Can-Grow XSB

## Textured Mulch Film

### DESCRIPTION:

Modified extra strong blend PE film

Can be downgauged to 0.5 mil to maximize coverage and minimize disposal costs.

High tensile strength for mechanical laying.

Embossing provides the elasticity and the traction to enable tight formation over raised beds.

Excellent moisture retention and weed reduction

Widths from 36 inch to 72 inch. 30000 sq.in./lb/mil Available in black, white/black, and silver/black.

### APPLICATION:

Raised-bed row mulching of vegetable crops, strawberries, melons, peppers.

PROPERTY	UNITS	TYPICAL VALUE	TEST METHOD
Thickness	mil	0.6	ASTM D-374
Opacity, in Black		100%	
Force @ 5% Stretch,	MD lb TD lb	1.37 1.48	ASTM D-882
Tensile at Break,	MD psi TD psi	5950 4930	ASTM D-882
Break Elongation,	MD % TD %	409 540	ASTM D-882
1% Secant Modulus,	MD psi TD psi	46412 52214	ASTM D-882
Elmendorf Tear,	MD g/mil TD g/mil	50 800	ASTM D-1922
Dart Impact (method A)	g/mil	200	ASTM D-1709

Imaflex makes no warranties in regard to the material (s) described herein, except that such material(s) shall conform to Imaflex's specifications either as in effect at the time of shipment or incorporated herein.