

IMAFLEX Can Block XSB

Textured v-TIF Fumigation Mulch Film

DESCRIPTION:

Modified HDPE v-TIF grade barrier film for fumigation applications

Available in 0.8 mil Black and .9 mil White on Black to maximize coverage and minimize disposal costs.

High tensile strength for mechanical laying.

Embossing provides the elasticity to enable tight formation over raised beds.

Excellent moisture retention and weed reduction in addition to barrier to fumigation gases

Widths from 36 inch to 66 inch.

APPLICATION:

Raised-bed row mulching of vegetable crops, strawberries, melons, peppers.

PROPERTY	UNITS		TYPICAL VALUE	METHODS
Thickness	Mils		0.80	ASTM D-6988
Opacity, in black	%		100	IMAFLEX
Tensile @ yield	MD	psi	2,320	ASTM D-882
	TD	psi	1,890	
Ultimate Tensile	MD	psi	4,230	ASTM D-882
	TD	psi	3,370	
Break Elongation	MD	%	355	ASTM D-882
	TD	%	400	
1% Secant Modulus	MD	psi	44,605	ASTM D-882
	TD	psi	48,200	
Elmendorf Tear	MD	g/mil	146	ASTM D-1922
	TD	g/mil	226	
Dart Drop (method A)	g/mil		235	ASTM D-1709

Imaflex makes no warranties in regard to the material (s) described herein, except that such material(s) shall conform to Imaflex's specifications either as in effect at the time of shipment or incorporated herein.